

The Glaciator X-Stream creates a total, ground fog effect from a self-contained unit. The Glaciator X-Stream utilizes the simple but effective Jem heavy fog fluids and a closed loop refrigeration system for a heavy fog solution.

- Density control: low, medium or high
- Continuous output
- 80 m² /min fog output
- 3500 W heat exchanger
- 15 min heat-up time
- 5 liter fluid capacity
- Different fluid options for different applications
- Internal or external fluid supply
- Low fluid sensing
- Self contained unit: no CO₂ or dry ice
- Onboard DMX
- On-board control panel
- Optional ducting system

Physical Length: 866 mm (34.1 in.)
 Width: 638 mm (25.1 in.)
 Height: 725 mm (28.5 in.)
 Dry weight: 110 kg (242.5 lbs.)

Performance Coverage volume: 80 m² per minute
 Operating time: Continuous, automatic level adjustment
 Warm-up time (approx.): 15 minutes

Control and Programming Control options: Onboard control panel, DMX
 Compatible remote controls: For limited control
 DMX channels: 2 (output and compressor)
 Protocol: USITT DMX512/1990

Construction Housing: Steel & aluminum
 Heat exchanger: 3500 W, direct thermal protection

Fluid System Fluid pump: Oscillating piston, high pressure X2
 Onboard fluid capacity: Internal 5 l reservoir
 External fluid supply: For larger volume remote fluid supply
 Fluid consumption at peak output: 120 ml per minute

Installation Orientation: Floor mount only (On wheels)

Connections Remote control: 3-pin locking XLR
 DMX data: 3-pin locking XLR
 Power cable entry: IEC-EN60309-2 Socket (Cee Type)

Electrical AC power (EU models): 220-240 V nominal, 50 Hz
 Main fuse (220-240 V power): Onboard 32 A Breaker
 AC power (US models): 208 V, 60 Hz
 Main Fuse (208 V power): Onboard 32 A Breaker

Thermal Maximum ambient temperature (Ta max.): 40° C (104° F)
 Exterior surface temperature, steady state: 50° C (122° F)
 Max. nozzle temperature: 200° C (392° F)

Approvals



EU safety: EN 50 081-1, EN 50 082-1
 EU safety: EN 60 335-1 (1995)

Included Items User manual: P/N 35010020
'C' form female socket for use with own power cable: P/N 05327240
Container 5 l: P/N 34300506

Accessories Heavy Fog (B2 mix) fluid
Heavy Fog (C3 mix)
JEM Multi-function (Analog) Remote Control: P/N 92765013
Ducting Kit incl. twin adapter and 2 x 5 m (16.4 ft.) ducting: P/N 92625007

Ordering Information Jem Glaciator X-Stream, 240 V: P/N 92210500
Jem Glaciator X-Stream, 208 V: P/N 92210501

Published on: 15 Oct 2008. © 2004-2008 Martin Professional A/S. Specifications subject to change without notice